

534 CR 529A Lake Panasoffkee, FL 33538 800-476-6674 352-793-1682 agri@uas-cropmaster.com www.uas-cropmaster.com



Section 1 - Product and Company Identification

Product	sc1200 + iron
Company	UAS of America
	534 CR 529A
	Lake Panasoffkee, FL 33538

Phone	800-476-6674

Emergency Phone 352-793-1682

Product Use Chelated Turf Special + Iron

Section 2 - Composition and Information on Ingredients

Component Ingredients	Hazardous	Percent	CAS Number	Threshold Limit Values	
				OSHA PEL STEL	ACGIH TLV STEL
Urea	No	12 %	57-13-6	-NONE EST	FABLISHED-
Ferrous Sulfate Heptahydrate	No	6 %	7782-63-0	-NONE EST	FABLISHED-
Manganese Sulfate Monohydrate	No	2 %	10034-96-5	-NONE EST	FABLISHED-

Section 3 - Hazard Identification

Potential Health Effects

This material is not a "health hazard" or "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration Hazard Communication Standard, 20 CFR 1910.1200

Section 4 - First Aid Measures Skin Contact Skin Absorption Eve Contact □ Inhalation Ingestion **Skin Contact** Dry and/or red itchy skin - Flush with water for 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation persists. Skin Absorption Dry and/or red itchy skin - Flush with water for 15 minutes. Get medical attention if irritation persists. **Eye Contact** Eye irritation - Flush with water for 15 minutes. Get medical attention if irritation persists. Inhalation Generally not considered an inhalation hazard. Ingestion Do not induce vomiting, contact a physician or poison control center.

Section 5 - Fire Fighting Measures

Flammable			
Flammable Conditions	None		
Methods of Extinguishing	Use media suitable to ex chemical.	tinguish source of fire. Water fog or spray,	, foam, carbon dioxide, or dry
Flashpoint degrees (c)	N/A		
Flashpoint Method	N/A		
Autolgnition Temp (c)	N/A	Upper Flammable Limit (% by volume)	N/A
		Lower Flammable Limit (% by volume)	N/A
Explosion - Sensitivity to Imp	pact		
N/A			
Explosion - Sensitivity to Sta N/A	tic Discharge		

Protection and Procedures for FireFighters Use water fog or spray, foam, carbon dioxide, or dry chemical to control fire.

Protective Equipment for Firefighters

Use approved self-contained breathing apparatus and full protective gear. Avoid smoke inhalation.

Section 6 - Accidental Release Measures

Leak and Spill Procedures

Environmental Precautions: Keep out of water supplies, lakes, ponds, streams, and rivers. Material Released or Spilled: Promptly mop up or pump up material and place in suitable container for use as a fertilizer or for proper disposal in accordance with local, state and federal regulations.

Section 7 - Handling and Storage

Handling Procedures and Equipment

Avoid contact with eyes. Use only in well ventilated areas. Wash thoroughly after handling. Avoid prolonged or repeated contact with the skin. Keep Out Of Reach Of Children. Other Precautions: Transfer using chemical-resistant plastic or stainless steel tanks, pumps, and valves.

Storage Requirements

Store in cool, dry area. Keep container closed when not in use. Keep Out Of Reach Of Children. Store in temperatures between 40 and 78 degrees F.

Section 8 - Exposure Controls - Personal Protection

Specific Engineering Controls

Adequate ventilation required to maintain a fresh airflow.

✓ Gloves	Respirator	🖌 Eye	✓ Footwear	Clothing	□ Other	

Personal Protective Equipment

Respiratory Protection: If mist or dust conditions should be present use respirator approved by NIOSH. Eye Protection: Goggles or face shield. Skin Protection: Adequate clothing should be worn to prevent skin contact. Other Protective Clothing or Equipment: Eye bath, safety shower. Work Hygienic Practices: Wash all clothing before wearing. Wash all exposed skin surfaces with soap and water after using this product.

Section 9 - Physical and Chemical Properties

Physical State	Liquid
Odor and Appearance	Dark Amber Liquid, Sweet Odor
Solubility in Water	Complete
Specific Gravity	1.4
Vapor Density (air = 1)	N/A
Vapor Pressure (mmHg)	N/A
Evaporation Rate	N/A
Boiling Point (° C)	212 F (F) 100 C (C)
Freezing Point (°C)	32 F (F) 0 C (C)
pH @ 20 Celcius	4.98-5.1
Coefficient of Water/Oil Distribution	N/A
Notes	11.63 lbs/gal

Section 10 - Stability and Reactivity

✓ Chemical Stability

Stability Conditions

Product is stable.

□ Incompatibility with Other Substance

Incombatiblity conditions

Strong oxidizing agents. Avoid contact with copper and aluminum. Water rinse sprayers after using.

Reactivity Conditions

Intense heate. Ferrous sulfate decomposes at 300 C

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide, metallic oxides, oxides of sulfur

Section 11 - Toxicological Information

Effects of Acute Exposure

Eye contact may cause irritation and redness.

Effects of Chronic Exposure

Prolonged contact with skin may cause irritation or dermatitis in sensitive individuals.

Irritancy	Slight		
Skin Sensitization	Redness	Respiratory Sensitize	Mild
Carcinogenicity - IARC	No	Carcinogenicity - ACGIH	No
Reproductive	No	Teratogenicity	No
Embrotoxicity	No	Mutagenicity	No

Section 12 - Ecological Information

Ecological Information

Not Known

Section 13 - Disposal Considerations

Waste Disposal

If product cannot be disposed of according to use directions on label. Dispose of in accordance with federal, state, and local environmental laws and regulations.

Section 14 - Transportation Information

U.S. DOT	Not Regulated
IMDG	Not Regulated
ICAO/IATA	Not Regulated

Transport Information

Other Shipping Description: Fertilizing Compounds (Manufactured), Liquid. NMFC Item 6810 Sub 6, LTL Class 70

Section 15 - Regulatory Information

Health Hazard	1	Exposure could cause irritation but only minor residual injury even if no treatment is given.
Fire Hazard	0	Materials that will not burn.
Instability	0	Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

Special Hazard

Section 16 - Other Information / Warranty / Disclaimer

Revised Prepared By	03-Feb	-15		Health Flammability Reactivity Personal Protection	1 0 0 B	ØV + 🗲
Health Hazard Flammability		1 0	Irritation or m Materials that	inor reversible injury will not burn	possit	ble

Reactivity	0	Materials that are normally stable, even under fire conditions, and will NOT react with water,
		polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection B Safety Glasses + Gloves

Disclaimer

HMIS Ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS ratings are not required on MSDS's by OSHA's CFR 1910.1200, we choose to provide them as a service to our customers using HMIS. These ratings are to be used only with a fully implemented HMIS program. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

NPCA recommends that employers must determine appropriate PPE for the actual conditions under which this product is used in their workplace. For information on PPE codes, consult the HMIS Implementation Manual.

When two ratings are provided for Health, the first represents the material 'as supplied,' and the second represents the material in use.'

Other Information

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and on the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the Vendee, the Vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, or furnishing of such information.